| | 91975 |
|---|-------------------------|
| Model number | DGC 6805 XL |
| Type of appliance | |
| Display | M Touch |
| | |
| | |
| Retractable dials | - |
| Gourmet advantages | |
| Electronic temperature regulation in oven mode from 30 - 225°C | • |
| Electronic temperature regulation in steam mode from 40 - 100°C | • |
| Oxygen sensor | • |
| Menu cooking with no transfer of flavours between different foods | • |
| Wireless food probe / Food probe with cable | •/- |
| Functions | |
| Automatic programmes | • |
| Combi cooking / Steam cooking | •/• |
| Full grill / Economy grill / Fan grill | •/•/• |
| Fan plus / Intensive bake / Cake plus | •/•/• |
| Conventional heat / Top heat / Bottom heat | •/•/• |
| Convenience features | |
| Motorised lift-up control panel | • |
| Automatic menu cooking | • |
| User programmes / Programmable settings | 20/• |
| Start-Stop programming | • |
| Clock display / Date display / Minute minder | •/•/• |
| Actual temperature display / Recommended temperatures | •/• |
| Appliance door | |
| CleanGlass door / ClearView door | •/• |
| Oven cavity | |
| Oven cavity volume in l | 48 |
| Removable side runners with PerfectClean finish | • |
| Number of halogen lights | 2 |
| Easy maintenance | |
| Stainless steel front with CleanSteel finish (CleanSteel appliances only) | • |
| Stainless steel oven cavity with PerfectClean / Linen finish | •/• |
| External steam generator | • |
| Maintenance programmes for Descaling / Soaking / Rinsing / Drying | •/•/• |
| Steam technology and water supply | |
| MultiSteam / MonoSteam | •/- |
| Water container with steam generator / Fresh water container | -/• |
| Condensate container behind motorised lift-up door | • |
| Mains water connection / Mains drainage connection | •/• |
| Efficiency and sustainability | |
| Energy efficiency class 1) | А |
| Low energy lighting / Rapid heat-up | •/• |
| Safety | · |
| Appliance cooling system and Cool front | • |
| Safety switch-off / System lock | •/• |
| Technical data | · |
| Niche dimensions in a tall unit in mm (W x H x D) 2) | 560-568 x 450-452 x 555 |
| Total connected load in kW / Voltage in V / Fuse rating in A | 3.4 / 230 / 20 |
| Accessories supplied | 3.4 / 230 / 20 |
| Universal tray with PerfectClean / Combi rack with PerfectClean | 1/1 |
| Perforated stainless steel containers / Solid stainless steel containers/ Condensate tray | 2/1/- |
| Stainless steel baking tray / Rack | -/- |
| Cookery book | -/- |
| Colours | • |
| Stainless steel/Clean Steel | • |
| Havana Brown | • |
| Brilliant White | ' |
| Obsidian Black | - |
| Obsidiali DidCK | |

¹⁾ Measured in accordance with EN 50304

N.B. Appliances must be installed in accordance with IEE regulations by a competent person.

²⁾ Please refer to the building-in diagrams for niche dimensions for building in with different appliances and units.